

HS-150S Premium Accelerometer




AC acceleration output via 4 Core Polyolefin HFFR with Protective Conduit

Key Features

- High Temperature
- Protective Conduit
- Premium design

Industries

Building services, Pulp and Paper,
Mining, Metals, Utilities, Automotive,
Water, Pharmaceutical



Technical Performance

Mounted Base Resonance	see 'How To Order' table (nominal)
Sensitivity	see: 'How To Order' table $\pm 10\%$ Nominal 80Hz at 72°F
Frequency Response	90cpm (1.5Hz) to 600kcpm (10kHz) $\pm 5\%$ 30cpm (0.5Hz) to 720kcpm (12kHz) $\pm 10\%$ 12cpm (0.2Hz) to 900kcpm (15kHz) $\pm 3\text{dB}$
Isolation	Base isolated
Range	see: 'How To Order' table
Transverse Sensitivity	Less than 5%

Mechanical

Case Material	Stainless Steel
Sensing Element/Construction	PZT/Shear
Mounting Torque	5.9ft. lbs
Mounting Bolt provided	see: 'How To Order' table x 1.4in long
Weight	7.2 oz. (nominal) body only
Maximum Cable Length	3,280 ft.
Standard Cable Length	16 ft.
Screened Cable	Polyolefin HFFR - length to be specified with order
Mounting Threads	see: 'How To Order' table
Submersible Depth	328 ft. max (10 bar)


Electrical

Excitation Voltage:	18-30Volts DC
Electrical Noise	0.1mg max
Current Range	0.5mA to 8mA
Bias Voltage	10 - 12 Volts DC
Settling Time	2 seconds
Output Impedance	200 Ohms max.
Case Isolation	$>10^8$ Ohms at 500 Volts

Environmental

Operating Temperature Range	-67 to 266°F
Sealing	IP68
Maximum Shock	5000g
EMC	EN61326-1:2013


Typical Frequency Response (at 100mV/g)



Applications

Fans, Motors, Pumps, Compressors,
Centrifuges, Conveyors, Air Handlers,
Gearboxes, Rolls, Dryers, Presses,
Cooling, VAC, Spindles, Machine Tooling,
Process Equipment

Vibration sensor should be firmly fixed to a flat surface
(spot face surface may be needed to be produced and
cable anchored to sensor body.)



How To Order

Product Prefix		Product Series											
HS - Hansford Sensors		150 - Premium Industrial Vibration Sensor											
H	S	1	5	0	S	X	X	X	X	X	X	X	
Extra Options (if required)					Sensitivity		Range		Resonant Frequency		Cable/Connector		Mounting Threads
F - Filtered					010 - 10mV/g		±800g		34kHz (2,040kcpm)		37C - 4 Core		02 - ¼-28" UNF Male
L - 316L Stainless Steel					030 - 30mV/g		±250g		33kHz (1,980kcpm)		Polyolefin HFFR with		06 - M6 x 1mm Male
RT - Temperature Output PT100					050 - 50mV/g		±160g		32kHz (1,920kcpm)		Protective Conduit		08 - M8 x 1.25mm Male
S - 90° Side Exit					100 - 100mV/g		±80g		30kHz (1,800kcpm)				
T - Temperature Output					250 - 250mV/g		±32g		28kHz (1,680kcpm)				
Y - 5% tolerance on sensitivity					500 - 500mV/g		±16g		26kHz (1,560kcpm)				



www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice

TS990U.3

