



AC acceleration and temperature output via FEP Cable with Protective Conduit

- Resistant to oil
- Protective Conduit
- Premium design


Building services, Pulp and Paper,
Mining, Metals, Utilities, Automotive,
Water, Pharmaceutical



| Technical Performance | | Mechanical | |
|------------------------|---|------------------------------|---|
| Mounted Base Resonance | see 'How To Order' table (nominal) | Case Material | Stainless Steel |
| Sensitivity | see: 'How To Order' table $\pm 10\%$ | Sensing Element/Construction | PZT/Compression |
| | Nominal 80Hz at 22°C | Mounting Torque | 8Nm |
| Frequency Response | 2Hz (120cpm) to 10kHz (600kcpm) $\pm 5\%$ | Mounting Bolt provided | see: 'How To Order' table x 30mm long |
| | 1.5Hz (90cpm) to 12kHz (720kcpm) $\pm 10\%$ | Weight | 185gms (nominal) body only |
| | 0.8Hz (48cpm) to 15kHz (900kcpm) $\pm 3\text{dB}$ | Screened Cable Assembly | see: www.hansfordsensors.com for options |
| Isolation | Base isolated | Maximum Cable Length | 1000 metres |
| Range | see: 'How To Order' table | Standard Cable Length | 5 metres |
| Temperature | 10 mV/ °C standard 100°C - Option 130°C | Mounting Threads | see: 'How To Order' table |
| Transverse Sensitivity | Less than 5% | Conduit Material | 316 Stainless Steel |
| | | Conduit Length | Conduit Length is approx. 0.5m shorter than the cable |

| Electrical | | Environmental | |
|---------------------|------------------------------------|-----------------------------|----------------|
| Excitation Voltage: | 18-30Volts DC | Operating Temperature Range | -55 to 140°C |
| Electrical Noise | 0.1mg max | Sealing | IP65 |
| Current Range | 0.5mA to 8mA | Maximum Shock | 5000g |
| Bias Voltage | 10 - 12 Volts DC | EMC | EN61326-1:2013 |
| Settling Time | 2 seconds | | |
| Output Impedance | 200 Ohms max. | | |
| Case Isolation | >10 ⁸ Ohms at 500 Volts | | |

Fans, Motors, Pumps, Compressors,
Centrifuges, Conveyors, Air Handlers,
Gearboxes, Rolls, Dryers, Presses,
Cooling, VAC, Spindles, Machine Tooling,
Process Equipment



| Product Prefix | | Product Series | | | Cable Length (if integral cable) | | | | | | | | | | | |
|---|----------|---|----------|---|----------------------------------|---|----------|---|----------|----------|---|----------|----------|----------|----------|----------|
| HS - Hansford Sensors | | 100 - Industrial Vibration Sensor | | | QXX - length specified in metres | | | | | | | | | | | |
| H | S | 1 | 0 | 0 | S | T | X | X | X | X | X | X | X | X | X | X |
| Extra Options (if required) F - Filtered L - 316L Stainless Steel RT - Temperature Output PT100 S - 90° Side Exit T - Temperature Output Y - 5% tolerance on sensitivity | | Sensitivity 010 - 10mV/g 030 - 30mV/g 050 - 50mV/g 100 - 100mV/g 250 - 250mV/g 500 - 500mV/g | | Range ±800g ±250g ±160g ±80g ±32g ±16g | | Resonant Frequency 27kHz (1,620kcpm) 25kHz (1,500kcpm) 23kHz (1,380kcpm) 21kHz (1,260kcpm) 19kHz (1,140kcpm) 17kHz (1,020kcpm) | | Cable/Connector 33C - FEP with Protective Conduit | | | Mounting Threads 02 - ¼-28" UNF Male 06 - M6 x 1mm Male 08 - M8 x 1.25mm Male | | | | | |



www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice

TS782.6

