

HS-AS Studs

isolation



Provides a barrier to cut down on electrical interference.

Mounting Studs provide a secure, permanent or semi-permanent point of connection

Part No.	Connection Point 1	Connction Point 2	Max Temp
HS-AS046-1	M6 x 1 Female	M6 x 1 Male	90 °C
HS-AS046-2	1/4"-28 UNF Female	1/4"-28 UNF Male	90 °C
HS-AS046-3	M8 x 1.25 Female	M8 x 1.25 Male	90 °C
HS-AS051-1/4	1/4"-28 UNF Male	1/4" - 28UNF Female Nylatron	145 °C
HS-AS051-M6	M6 x 1 Male	M6 x 1 Female Nylatron	145 °C
HS-AS051-M8	M8 x 1.25 Male	M8 x 1.25 Female Nylatron	145 °C
HS-AS051-M8X1.25	M8 x 1.00 Male	M8 x 1.25 Female Nylatron	145 °C
HS-AS051-M10	M10 x 1.5 Male	M10 x 1.5 Female Nylatron	145 °C
HS-AS051-M10X1.25	M10 x 1.25 x 10mm Male	M10 x 1.25 Female Nylatron	145 °C



HS-AS Studs

isolation



Provides a barrier to cut down on electrical interference.

Mounting Studs provide a secure, permanent or semi-permanent point of connection

Part No.	Connection Point 1	Connection Point 2	Max Temp
HS-AS061-1/4	1/4"-28 UNF Male	1/4"-28 UNF Female Peek	250 °C
HS-AS061-M6	M6 x 1 Male	M6 x 1 Female Peek	250 °C
HS-AS061-M8	M8 x 1.25 Male	M8 x 1.25 Female Peek	250 °C

