

HS-AS Studs

mounting/grub screws



Screw studs for use to adapt a female thread into a male thread.

Mounting Studs provide a secure, permanent or semi-permanent point of connection

Part No.	Connection Point 1	Connection Point 2			
HS-AS008	1/4"-28 UNF Male	M8 Male x 1.25 Stop & Slot x 0.4in Long			
HS-AS020	10-32 UNF x 0.4in Long Male Hex Socket Drive				
HS-AS021	1/4"-28 UNF Male	M10 Male x 1.50 Stop & Slot x 0.4in Long			
HS-AS022	1/4"-28 UNF Male	1/4"-28 UNF 1/2" Male Hex Stop & Slot x 0.4in Long			
HS-AS023	1/4"-28 UNF Male	M8 Male x 1.25 x 0.3in Long			
HS-AS024	1/4"-28 UNF Male	M6 Male x 1 Stop & Slot x 0.4in Long			
HS-AS025	1/4"-28 UNF Male	3/8"-24 UNF Male x 0.6in Overall Length			
HS-AS043	1/4"-28 UNF Male	10-32 UNF Male x 0.4in Long			
HS-AS053	1/4"-28 UNF Male	M6 Male x 0.04in x 0.4in Long			
HS-AS076	1/2"-20 UNF Male	M6 Male with Screwdriver Slot x 0.3 in			
HS-AS081	1/4"-28 UNF Male	M12 Male x 0.06in x 0.4in Overall Length			
HS-AS083	1/4"-28 UNF Male	M10 Male x 0.06in x 0.5in Long			

HS-AS Studs

mounting/grub screws

Part No.	Connection Point 1	Connection Point 2			
HS-AS084	1/4"-28 UNF Male	M5 Male x 0.8 x 0.4in Long			
HS-AS086	1/4"-28 UNF Male	M8 x 1 Male Stop & Slot x 0.4in Long			
HS-AS090	1/4"-28 UNF Male	M10 x 1.25 Male x 0.4in Long			
HS-AS101	1/4"-28 UNF Male	1/2"-20 UNF Male with Screwdriver Slot x 0.3in Long			
HS-AS102	1/4"-28 UNF Male	1/2"-20 UNF Male with Screwdriver Slot x 0.3in Long			Brass
HS-AS104	1/4"-28 UNF Male	M6 Male x 1 x 0.3in Long			
HS-AS110	1/4"-28 UNF Male	M10 x 1.25 Male x 0.5in Long			
HS-AS112	1/4"-28 UNF Male	M12 x 1.5 Male x 0.7in Long			
HS-AS115	1/4"-28 UNF Male	1/2" - 13 TPI UNC x 1" Male			
HS-AS122	1/4"-28 UNF Male	M10 x 1 Male Stop & Slot x 0.5in Long			
HS-AS208	1/4"-28 UNF x 0.5in Long Male Hex Socket Drive				