

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification System for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx BAS 18.0082X** Page 1 of 5

Certificate history: Issue 3 (2020-06-11)

Status: Current Issue No: 4

Issue 2 (2020-01-16)

Date of Issue:

Applicant:

2023-04-21

Issue 1 (2019-03-22) Issue 0 (2018-11-09)

Hansford Sensors Limited Artisan

Hillbottom Road

Sands Industrial Estate

Bucks HP12 4HJ **United Kingdom**

Equipment:

HS-150I & HS170I Series Accelerometers

Optional accessory:

Type of Protection: **Intrinsic Safety**

See Certificate Schedule for Marking Details Marking:

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Technical Manager

Position:

Signature: (for printed version)

21/4/2023

(for printed version)

This certificate and schedule may only be reproduced in full.
This certificate is not transferable and remains the property of the issuing body.
The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

SGS UK Limited Rockhead Business Park Staden Lane **Buxton, Derbyshire SK17 9RZ United Kingdom**





IECEx Certificate of Conformity

Page 2 of 5 Certificate No.: **IECEx BAS 18.0082X**

Date of issue: 2023-04-21 Issue No: 4

Manufacturer: Hansford Sensors Limited.

Artisan

Hillbottom Road

Sands Industrial Estate

Bucks HP12 4HJ United Kingdom

Manufacturing

Hansford Sensors Limited.

locations: Artisan

Hillbottom Road

Sands Industrial Estate

Bucks HP12 4HJ **United Kingdom**

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"

Edition:6.0

This Certificate does not indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

GB/BAS/ExTR18.0244/00 GB/BAS/ExTR19.0059/00 GB/BAS/ExTR19.0347/00

GB/BAS/ExTR19.0347/01 GB/SGS/ExTR23.0010/00

Quality Assessment Report:

GB/BAS/QAR07.0040/10



IECEx Certificate of Conformity

Certificate No.: IECEx BAS 18.0082X Page 3 of 5

Date of issue: 2023-04-21 Issue No: 4

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The HS-150i and HS-170i Series Accelerometers are designed to measure acceleration or vibration by converting the signal generated by the compression of a Piezo electric crystal by a given seismic mass and outputting a broadband ac signal to the monitoring equipment.

The accelerometer comprises of a piezo electric crystal connected to a signal conditioning board, all contained within a fully welded steel enclosure.

HS-150xT versions include a temperature transmitter.

HS-173 is a tri-axial accelerometer comprising three individual circuits with common 0V line, sharing a single set of parameters.

Electrical connections are made via a connector or integral cable. The equipment carries the following markings:

SPECIFIC CONDITIONS OF USE: YES as shown below:

- 1. Where equipment is supplied with an attached cable, this must be terminated in an enclosure providing at least degree of protection IP20.
- 2. The equipment is marked with reduced certification markings. Refer to the Certificate Schedule for the full certification markings & applicable temperature classification and associated ambient temperature range.



IECEx Certificate of Conformity

Certificate No.: IECEx BAS 18.0082X Page 4 of 5

Date of issue: 2023-04-21 Issue No: 4

Equipment (continued):

Uni-axial accelerometers with integral cable

Ex ia IIC T6 Ga -55°C \leq Ta \leq +57°C Ex ia IIC T4 Ga -55°C \leq Ta \leq +103°C

Ex ia IIIC T₂₀₀110°C Da -55°C ≤ Ta ≤ +57°C Ex ia IIIC T₂₀₀135°C Da -55°C ≤ Ta ≤ +70°C Ex ia IIIC T₂₀₀145°C Da -55°C ≤ Ta ≤ +92°C

Ex ia I Ma -55°C ≤ Ta ≤ +103°C

Uni-axial accelerometers with connectors

Ex ia IIC T6 Ga -55°C \leq Ta \leq +57°C Ex ia IIC T4 Ga -55°C \leq Ta \leq +103°C

Ex ia IIIC $T_{200}135^{\circ}$ C Da -55°C \leq Ta \leq +70°C

Ex ia IIIB $T_{200}110^{\circ}C$ Da -55°C \leq Ta \leq +57°C Ex ia IIIB $T_{200}145^{\circ}C$ Da -55°C \leq Ta \leq +92°C

Ex ia I Ma -55°C ≤ Ta ≤ +103°C

Tri-axial Accelerometers with integral cable.

Ex ia IIC T6 Ga -55°C \leq Ta \leq +69°C Ex ia IIC T4 Ga -55°C \leq Ta \leq +104°C

Ex ia IIIC T₂₀₀102°C Da -55°C \leq Ta \leq +69°C Ex ia IIIC T₂₀₀131°C Da -55°C \leq Ta \leq +98°C

Ex ia I Ma -55°C ≤ Ta ≤ +104°C

Triaxial accelerometers with connectors.

Ex ia IIC T6 Ga -55°C \leq Ta \leq +69°C Ex ia IIC T4 Ga -55°C \leq Ta \leq +104°C

Ex ia IIIC $T_{200}135^{\circ}$ C Da -55°C \leq Ta \leq +70°C

Ex ia IIIB $T_{200}102^{\circ}C$ Da -55 $^{\circ}C \le Ta \le +69^{\circ}C$ Ex ia IIIB $T_{200}131^{\circ}C$ Da -55 $^{\circ}C \le Ta \le +98^{\circ}C$

Ex ia I Ma -55°C \leq Ta \leq +104°C See Certificate Annex for terminal parameters.



IECEx Certificate of Conformity

Certificate No.: IECEx BAS 18.0082X Page 5 of 5

Date of issue: 2023-04-21 Issue No: 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above) Variation 4.1

This issue of the certificate permits a revision of the terminal parameters to reflect altered maximum lengths of integral cable.

ExTR: GB/BAS/ExTR19.0347/02 File Reference: 23/0237

Annex:

IECEx BAS 18.0082X Annex 3.pdf

SGS Baseefa Limited

Rockhead Business Park Staden lane, Buxton, Derbyshire SK17 9RZ United Kingdom



Date: 19 April 2023

ANNEX to IECEx BAS 18.0082X

Issue No. 3

The HS-150i and HS-170i Series Accelerometers

The equipment has the following terminal parameters:

Uni-axial accelerometer.

Connector Only	≤ 10m of Cable	≤ 150m ofC able	≤ 300m of Cable
$\begin{array}{rcl} U_i & = & 28 \ V \\ I_i & = & 93 \ mA \\ P_i & = & 0.65 \ W \\ C_i & = & 1.2 \ nF \\ L_i & = & 0 \end{array}$	$\begin{array}{rcl} U_i & = & 28 \ V \\ I_i & = & 93 \ mA \\ P_i & = & 0.65 \ W \\ C_i & = & 5.2 \ nF \\ L_i & = & 10 \ \mu H \end{array}$	$\begin{array}{rcl} U_i & = & 28 \ V \\ I_i & = & 93 \ mA \\ P_i & = & 0.65 \ W \\ C_i & = & 61.2 \ nF \\ L_i & = & 150 \ \mu H \end{array}$	$\begin{array}{rcl} U_i & = & 28 \ V \\ I_i & = & 93 \ mA \\ P_i & = & 0.65 \ W \\ C_i & = & 64.2 \ nF \\ L_i & = & 150 \ \mu H \end{array}$

Tri-axial accelerometer

Connector Only	≤ 10m of Cable	≤ 150mo f Cable	≤ 300m of Cable
$I_i = 93 \text{m A}$ $P_i = 0.65 \text{ W}$ $C_i = 3.6 \text{ nF}$	$\begin{array}{lll} U_i & = & 28 \ V \\ I_i & = & 93 \ mA \\ P_i & = & 0.65 \ W \\ C_i & = & 7.6 \ nF \\ L_i & = & 10 \ \mu H \end{array}$	$\begin{array}{rcl} U_i & = & 28 \ V \\ I_i & = & 93 \ mA \\ P_i & = & 0.65 \ W \\ C_i & = & 63.6 \ nF \\ L_i & = & 150 \ \mu H \end{array}$	$\begin{array}{rcl} U_i & = & 28 \ V \\ I_i & = & 93 \ mA \\ P_i & = & 0.65 \ W \\ C_i & = & 66.6 \ nF \\ L_i & = & 150 \ \mu H \end{array}$