

HS-420 Accelerometer



4-20mA velocity output via 4 Core Polyolefin HFFR

Key Features

- Halogen free cable
- Resistant to oil
- For use with PLC/DCS systems

Industries

Building services, Pulp and Paper,
Mining, Metals, Utilities, Automotive,
Water, Pharmaceutical



Technical Performance

| | |
|------------------------|--|
| Mounted Base Resonance | 5kHz min |
| Velocity Ranges | see: 'How To Order' table $\pm 10\%$ Nominal 80Hz at 22°C |
| Frequency Response | 10Hz (600cpm) to 1kHz (60kcpm) $\pm 5\%$ - ISO10816 |
| Isolation | Base isolated |
| Range | 50g peak |
| Transverse Sensitivity | Less than 5% |

Mechanical

| | |
|------------------------------|---|
| Case Material | Stainless Steel |
| Sensing Element/Construction | PZT/Compression |
| Mounting Torque | 8Nm |
| Weight | 100gms (nominal) body only |
| Maximum Cable Length | 1000 metres |
| Standard Cable Length | 5 metres |
| Screened Cable | Polyolefin HFFR - length to be specified with order |
| Mounting Threads | see: 'How To Order' table |


Electrical

| | |
|------------------|---|
| Current Output | 4-20mA DC proportional to Velocity Range |
| Supply Voltage | 15-30 Volts DC (for 4-20mA) |
| Settling Time | 2 seconds |
| Output Impedance | Loop Resistance 600 Ohms max. at 24 Volts |
| Case Isolation | $>10^8$ Ohms at 500 Volts |

Environmental

| | |
|-----------------------------|----------------|
| Operating Temperature Range | -55 to 130°C |
| Sealing | IP68 |
| Maximum Shock | 5000g |
| EMC | EN61326-1:2013 |


Typical Frequency Response



Applications

Fans, Motors, Pumps, Compressors,
Centrifuges, Conveyors, Air Handlers,
Gearboxes, Rolls, Dryers, Presses,
Cooling, VAC, Spindles, Machine Tooling,
Process Equipment

Vibration sensor should be firmly fixed to a flat surface
(spot face surface may be needed to be produced and
cable anchored to sensor body.)



How To Order

| Product Prefix HS - Hansford Sensors | | Product Series 420 - Industrial Vibration Sensor | | | | | Cable Length (if integral cable) QXX - length specified in metres | | | | | | | |
|--|---|---|---|---|---|---|--|--------------------------------|---|---|---|---|---|---|
| H | S | 4 | 2 | 0 | X | X | X | X | X | X | X | X | X | X |
| Extra Options (if required) | | | | | Velocity Range (RMS unless specified) | | | Cable/Connector | | | Mounting Threads | | | |
| F - Filtered L - 316L Stainless Steel RT - Temperature Output PT100 S - 90° Side Exit T - Temperature Output | | | | | P - Peak Range PP - Peak to Peak Range | | | 37 - 4 Core Polyolefin HFFR | | | 01 - 1/4-28" UNF Female 02 - 1/4-28" UNF Male 05 - Quick Fit Female 06 - M6 x 1mm Male 08 - M8 x 1.25mm Male 10 - M10 x 1.5mm Male | | | |



www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice
TS1065.5

