

HS-150H Premium High Temperature Accelerometer


AC acceleration output via M12 Connector

Key Features

- For use with data collector
- Premium design
- Customisable features

Industries

Building services, Pulp and Paper,
Mining, Metals, Utilities, Automotive,
Water, Pharmaceutical



Technical Performance

Mounted Base Resonance	see 'How To Order' table (nominal)
Sensitivity	see: 'How To Order' table $\pm 10\%$ Nominal 80Hz at 22°C
Frequency Response	2Hz (120cpm) to 10kHz (600kcpm) $\pm 5\%$ 1.5Hz (90cpm) to 12kHz (720kcpm) $\pm 10\%$ 0.8Hz (48cpm) to 15kHz (900kcpm) $\pm 3\text{dB}$
Isolation	Base isolated
Range	see: 'How To Order' table
Transverse Sensitivity	Less than 5%

Mechanical

Case Material	Stainless Steel
Sensing Element/Construction	PZT/Shear
Mounting Torque	8Nm
Weight	106gms (nominal) body only
Screened Cable Assembly	see: www.hansfordsensors.com for options
Connector	HS-AC010 - straigh HS-AC011 - right angle
Mounting Threads	see: 'How To Order' table


Electrical

Excitation Voltage:	18-30Volts DC
Electrical Noise	0.1mg max
Current Range	0.5mA to 8mA
Bias Voltage	10 - 12 Volts DC
Settling Time	2 seconds
Output Impedance	200 Ohms max.
Case Isolation	$>10^8$ Ohms at 500 Volts

Environmental

Operating Temperature Range	-55 to 165°C
Sealing	IP67
Maximum Shock	5000g
EMC	EN61326-1:2013


Typical Frequency Response (at 100mV/g)



Applications

Fans, Motors, Pumps, Compressors,
Centrifuges, Conveyors, Air Handlers,
Gearboxes, Rolls, Dryers, Presses,
Cooling, VAC, Spindles, Machine Tooling,
Process Equipment

Vibration sensor should be firmly fixed to a flat surface
(spot face surface may be needed to be produced and
cable anchored to sensor body.)



How To Order

Product Prefix	Product Series											
HS - Hansford Sensors	150 - Premium Industrial Vibration Sensor	H	S	1	5	0	H	X	X	X	X	X
Extra Options (If required)	Sensitivity	Range	Resonant Frequency	Cable/Connector	Mounting Threads							
F - Filtered	010 - 10mV/g	$\pm 800\text{g}$	34kHz (2,040kcpm)	01 - PUR	01 - 1/4-28" UNF Female							
L - 316L Stainless Steel	030 - 30mV/g	$\pm 250\text{g}$	33kHz (1,980kcpm)	02 - Braided	02 - 1/4-28" UNF Male							
RT - Temperature Output PT100	050 - 50mV/g	$\pm 160\text{g}$	32kHz (1,920kcpm)	07 - Silicon	05 - Quick Fit Female							
S - 90° Side Exit	100 - 100mV/g	$\pm 80\text{g}$	30kHz (1,800kcpm)	08 - Flame Retardant	06 - M6 x 1mm Male							
T - Temperature Output	250 - 250mV/g	$\pm 32\text{g}$	28kHz (1,680kcpm)	50 - 2 Pin MS	08 - M8 x 1.25mm Male							
Y - 5% tolerance on sensitivity	500 - 500mV/g	$\pm 16\text{g}$	26kHz (1,560kcpm)	54 - M12	10 - M10 x 1.5mm Male							
H - High Temperature												



www.hansfordsensors.com
sales@hansfordsensors.com

We reserve the right to alter the specification of this product without prior notice

TS693.1

