


HS-558 4 Channel Interface Module

μ A/g to mV/g convertor

Key Features

- Current line drive to AC voltage converter
- 4 Channels
- TDX Ok function
- Din Rail mounted



Connection Details

1. Sensor 1. 0V IN
2. Sensor 1. +ve IN
3. Sensor 2. 0V IN
4. Sensor 2. +ve IN
5. Sensor 3. 0V IN
6. Sensor 3. +ve IN
7. Sensor 4. 0V
8. Sensor 4. +ve IN
9. 100mV/g OUT Sensor 4.
10. 100mV/g OUT Sensor 3.
11. 100mV/g OUT Sensor 2.
12. 100mV/g OUT Sensor 1.
13. +24V Power IN
14. 0V Power IN
15. +24V Power OUT
16. 0V Power OUT

Technical Performance

Input	10 μ A or 50 μ A Line drive accelerometer see: 'How To Order' table
Output	100 mV/g
DC Bias	12V (nominal)
Sensor Fault	DC Bias indicates 24V

Mechanical

Case Material	Plastic
Mounting	DIN Rail TS35 (Top Hat)
Dimensions	111 x 99 x 22.6 mm (4.4 x 3.9 x 0.9 in) (H x D x W)
Connections	Screw Clamp
Conductor Size	0.5 to 5.0 mm (0.02 to 0.2 in)
Weight	140 gms (4.9 oz.) (nom)

Electrical

Power Input	+24 V DC @ 50 mA (from HS-570 Power Supply Module)
-------------	--

Environmental

Operating Temperature Range	0 to 55 °C (32 to 131°F)
Installation Category (IEC664)	II
Equipment Class (IEC536)	III
EMC	EN61326-1:2013

How To Order

